



sectional drawing A-A





Scale - 3:1

Order Code	L1 (mm)	W (mm)	ØD (mm)	ØID closed (mm)
500 910 500	6.8 ± 0.3	6.5 ± 0.3	3.8 ± 0.2	3.0 ± 0.2
500 911 000	8.2 ± 0.3	9.2 ± 0.3	5.4 ± 0.3	3.0 ± 0.2
500 912 000	8.9 ± 0.3	13.2 ± 0.3	5.4 ± 0.3	3.0 ± 0.2
500 912 500	6.4 ± 0.3	6.3 ± 0.3	3.7 ± 0.2	3.5 ± 0.2
500 913 000	10.2 ± 0.3	10.0 ± 0.3	5.4 ± 0.3	4.5 ± 0.2
500 913 500	10.2 ± 0.3	9.3 ± 0.3	5.0 ± 0.3	6.2 ± 0.3
500 915 500	13.2 ± 0.3	12.3 ± 0.3	5.4 ± 0.3	9.0 ± 0.3
500 916 500	16.0 ± 0.3	12.9 ± 0.3	5.4 ± 0.3	12.8 ± 0.3
500 917 000	17.1 ± 0.3	12.9 ± 0.3	4.8 ± 0.2	15.5 ± 0.3
500 917 500	20.2 ± 0.4	12.9 ± 0.3	5.4 ± 0.3	17.0 ± 0.3
500 918 000	21.2 ± 0.4	12.9 ± 0.3	5.4 ± 0.3	20.0 ± 0.3

Operating Temperatur: -30°C up to +85°C

				Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions
				Max-Eyth-Str. 1 74638 Waldenburg
				Germany com. +49 79 42 945 - 0
				www.we-online.de
REV.	FILE	DATE	BY	eiSos@we-online.de würth

	CREATED DaF	CHECKED SKI	GENERAL TOLERANCE DIN ISO 2768-1m		PROJECTION METHOD			SIZE A4
	DESCRIPTION			L REFERE	NCE	MATERIAL		
	AsCHCL	AsCHCL Cable Clip				Nylon 66, natural		
	Cable Clip				ORDER CODE			
<u>-</u>				500 91x x00				
<u></u>	SIZE	WEIGHT	STATUS	DATE		BUSINES	SS UNIT	PAGE
)- IK	xxx xxx xxx		Released	2016-09	-01	eiC	an	1 /1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Wurth Electronics:

 $\frac{500911000}{500912500} \ \frac{500912500}{500910500} \ \frac{500913000}{500911500} \ \frac{500914000}{500916500} \ \frac{500915000}{500918000} \ \frac{500915500}{500916000} \ \frac{500912000}{500918500} \ \frac{500917500}{500918500}$