



Radial Lead Type

Series : **KA** Type : **A**

Low Profile



Features

- Endurance : 85 °C 1000 h
- 7 mm height
- RoHS compliant


Specifications

Category temperature range	-40 °C to +85 °C	
Rated voltage range	4 V.DC to 50 V.DC	
Capacitance range	2.2 μF to 470 μF	
Capacitance tolerance	±20 % (120 Hz/+20 °C)	
Leakage current	$I \leq 0.01 CV$ or 3 (μA) After 2 minutes (Whichever is greater)	
Dissipation factor (tan δ)	Please see the attached characteristics list	
Endurance	After applying rated working voltage for 1000 hours at +85 °C±2 °C when the capacitors are restored to 20 °C, capacitors shall meet the following limits.	
	Capacitance change	Within ±20 % of the initial value
	tan δ	≤ 200 % of the initial limit
	DC leakage current	Within the initial limit
Shelf life	After storage for 1000 hours at +85 °C±2 °C with no voltage applied and then being stabilized at +20 °C, capacitors shall meet the limits specified in Endurance (With voltage treatment)	

Frequency correction factor for ripple current

Frequency (Hz)	50, 60	120	1 k	10 k to
Correction factor	0.70	1.00	1.30	1.70

Dimensions



(Unit : mm)

ϕD	4	5	6.3	8
ϕd	0.45	0.45	0.45	0.45
F	1.5	2.0	2.5	2.5

Characteristics list

Endurance : 85 °C 1000 h

Rated voltage (V.DC)	Cap. (±20 %) (μF)	Case size (mm)		Specification		Lead length (mm)			Part No.	Min. Packaging Q'ty		
		φD	L	Ripple current (120 Hz) (+85 °C) (mA r.m.s.)	tan δ (120 Hz) (+20 °C)	Lead dia. φd	Lead space			Straight leads (pcs)	Taping (pcs)	
							Straight	Taping *B				Taping *i
4	47	4	7	34	0.35	0.45	1.5	5.0	2.5	ECEA0GKA470()	200	2000
	100	5	7	61	0.35	0.45	2.0	5.0	2.5	ECEA0GKA101()	200	2000
	220	6.3	7	82	0.35	0.45	2.5	5.0	2.5	ECEA0GKA221()	200	2000
	330	8	7	110	0.35	0.45	2.5		2.5	ECEA0GKA331()	200	1000
		8	7	110	0.35	0.45		5.0		ECEA0GKA331Q		1000
	470	8	7	140	0.35	0.45	2.5		2.5	ECEA0GKA471()	200	1000
8		7	140	0.35	0.45		5.0		ECEA0GKA471Q		1000	
6.3	47	4	7	46	0.24	0.45	1.5	5.0	2.5	ECEA0JKA470()	200	2000
	100	5	7	71	0.24	0.45	2.0	5.0	2.5	ECEA0JKA101()	200	2000
	220	6.3	7	103	0.24	0.45	2.5	5.0	2.5	ECEA0JKA221()	200	2000
	330	8	7	130	0.24	0.45	2.5		2.5	ECEA0JKA331()	200	1000
		8	7	130	0.24	0.45		5.0		ECEA0JKA331Q		1000
10	33	4	7	43	0.20	0.45	1.5	5.0	2.5	ECEA1AKA330()	200	2000
	100	6.3	7	80	0.20	0.45	2.5	5.0	2.5	ECEA1AKA101()	200	2000
	220	8	7	120	0.20	0.45	2.5		2.5	ECEA1AKA221()	200	1000
		8	7	120	0.20	0.45		5.0		ECEA1AKA221Q		1000
16	10	4	7	28	0.16	0.45	1.5	5.0	2.5	ECEA1CKA100()	200	2000
	22	4	7	39	0.16	0.45	1.5	5.0	2.5	ECEA1CKA220()	200	2000
	33	5	7	60	0.16	0.45	2.0	5.0	2.5	ECEA1CKA330()	200	2000
	47	5	7	70	0.16	0.45	2.0	5.0	2.5	ECEA1CKA470()	200	2000
	100	6.3	7	91	0.16	0.45	2.5	5.0	2.5	ECEA1CKA101()	200	2000
25	10	4	7	28	0.14	0.45	1.5	5.0	2.5	ECEA1EKA100()	200	2000
	22	5	7	55	0.14	0.45	2.0	5.0	2.5	ECEA1EKA220()	200	2000
	33	6.3	7	65	0.14	0.45	2.5	5.0	2.5	ECEA1EKA330()	200	2000
	47	6.3	7	70	0.14	0.45	2.5	5.0	2.5	ECEA1EKA470()	200	2000
35	10	5	7	30	0.12	0.45	2.0	5.0	2.5	ECEA1VKA100()	200	2000
	22	6.3	7	60	0.12	0.45	2.5	5.0	2.5	ECEA1VKA220()	200	2000
	33	6.3	7	65	0.12	0.45	2.5	5.0	2.5	ECEA1VKA330()	200	2000
	47	8	7	85	0.12	0.45	2.5		2.5	ECEA1VKA470()	200	1000
		8	7	85	0.12	0.45		5.0		ECEA1VKA470Q		1000
50	2.2	4	7	16	0.10	0.45	1.5	5.0	2.5	ECEA1HKA2R2()	200	2000
	3.3	4	7	18	0.10	0.45	1.5	5.0	2.5	ECEA1HKA3R3()	200	2000
	4.7	4	7	23	0.10	0.45	1.5	5.0	2.5	ECEA1HKA4R7()	200	2000
	10	5	7	35	0.10	0.45	2.0	5.0	2.5	ECEA1HKA100()	200	2000
	22	6.3	7	60	0.10	0.45	2.5	5.0	2.5	ECEA1HKA220()	200	2000
	33	8	7	75	0.10	0.45	2.5		2.5	ECEA1HKA330()	200	1000
8		7	75	0.10	0.45		5.0		ECEA1HKA330Q		1000	

· When requesting taped product, please put the letter "B" or "i" between the "()". Lead wire pitch *B=5 mm, i=2.5 mm.

· Please refer to the page of "Taping dimensions".

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[ECE-A1HKA100](#) [ECE-A1HKA220](#) [ECE-A1HKA2R2](#) [ECE-A0JKA101](#) [ECE-A0JKA221](#) [ECE-A0JKA330](#) [ECE-A0JKA331](#) [ECE-A0JKA470](#) [ECE-A1CKA100](#) [ECE-A1CKA101](#) [ECE-A1CKA220](#) [ECE-A1CKA330](#) [ECE-A1CKA470](#) [ECE-A1EKA470](#) [ECE-A1AKA101](#) [ECE-A1AKA101I](#) [ECE-A1AKA221](#) [ECE-A1EKA100](#) [ECE-A1EKA220](#) [ECE-A1HKA4R7B](#) [ECE-A1VKA100](#) [ECE-A1VKA220](#) [ECE-A1VKA330](#) [ECE-A1VKA100B](#) [ECE-A1AKA470](#) [ECE-A1CKA101B](#) [ECE-A1HKA4R7I](#) [ECE-A0GKA101](#) [ECE-A0GKA101B](#) [ECE-A0GKA101I](#) [ECE-A0GKA221](#) [ECE-A0GKA221B](#) [ECE-A0GKA221I](#) [ECE-A0GKA331](#) [ECE-A0GKA331I](#) [ECE-A0GKA331Q](#) [ECE-A0GKA470](#) [ECE-A0GKA470B](#) [ECE-A0GKA470I](#) [ECE-A0GKA471](#) [ECE-A0GKA471I](#) [ECE-A0GKA471Q](#) [ECE-A0JKA101B](#) [ECE-A0JKA220](#) [ECE-A0JKA220B](#) [ECE-A0JKA221B](#) [ECE-A0JKA221I](#) [ECE-A0JKA330B](#) [ECE-A0JKA330I](#) [ECE-A0JKA331I](#) [ECE-A0JKA331Q](#) [ECE-A0JKA470B](#) [ECE-A0JKA470I](#) [ECE-A1AKA101B](#) [ECE-A1AKA220](#) [ECE-A1AKA220B](#) [ECE-A1AKA220I](#) [ECE-A1AKA221I](#) [ECE-A1AKA221Q](#) [ECE-A1AKA330](#) [ECE-A1AKA330B](#) [ECE-A1AKA330I](#) [ECE-A1AKA470B](#) [ECE-A1AKA470I](#) [ECE-A1CKA100B](#) [ECE-A1CKA100I](#) [ECE-A1CKA220B](#) [ECE-A1CKA220I](#) [ECE-A1CKA330B](#) [ECE-A1CKA330I](#) [ECE-A1CKA470B](#) [ECE-A1CKA470I](#) [ECE-A1EKA100B](#) [ECE-A1EKA100I](#) [ECE-A1EKA220B](#) [ECE-A1EKA220I](#) [ECE-A1EKA330](#) [ECE-A1EKA330B](#) [ECE-A1EKA330I](#) [ECE-A1EKA470B](#) [ECE-A1EKA470I](#) [ECE-A1EKA4R7](#) [ECE-A1EKA4R7B](#) [ECE-A1EKA4R7I](#) [ECE-A1HKA010](#) [ECE-A1HKA010B](#) [ECE-A1HKA010I](#) [ECE-A1HKA100B](#) [ECE-A1HKA100I](#) [ECE-A1HKA220B](#) [ECE-A1HKA220I](#) [ECE-A1HKA2R2B](#) [ECE-A1HKA2R2I](#) [ECE-A1HKA330I](#) [ECE-A1HKA330Q](#) [ECE-A1HKA3R3](#) [ECE-A1HKA3R3B](#) [ECE-A1HKA3R3I](#) [ECE-A1HKA4R7](#) [ECE-A1VKA100I](#)