


**D-Sub connectors - Stamped and Formed Contacts** 





#### **Specifications**

• Connectors according to: MIL C24308

Steel with nickel plating	
4V-0	
ting	

	Electrical Data
Current rating	5A
Voltage rating	600V AC/rms 50Hz
Withstanding voltage	1000V AC/rms 50HZ for one minute
Insulation resistance	5000ΜΩ
Contact resistance	10mΩ Max.

Climatic Data		
Operating temperature	-55°C to +125°C	

#### **Mechanical Data**

#### Mating and unmating force

Unit: kg (lb)

No. of Cts	Mate (max)	Unmate (min)
15	3.81 (8.42)	0.52 (1.14)
26	5.95 (13.16)	1.05 (2.32)
44	9.26 (20.46)	1.37 (3.02)
62	13.48 (29.78)	1.76 (3.88)

Standard plating thickness

- gold flash
- 0.4µm (15µ") gold
- 0.76µm (30µ") gold

Amphenol's high density
D-Sub connectors complement
Amphenol's extensive D-Sub
connector line. This line offers many
superior features, high performance
level and low installation cost.

The decreased contact spacing accommodates greater signal density in comparison to conventional D-Sub connectors.

Economical right angle PCB


Industrial


- Telecom
- Any industry standard I / O connections







# P.C.B. Layout








# **Panel mounting option**




Front female screwlock


4F / 3F



Threaded rear insert 4R / 3R


# **Shell size dimensions**





NB OF	DIMENSIONS mm (inch)			
CONTACTS	Α	В	С	D
15	30.84 (1.214)	24.99 (.984)	16.26 (.640)	2.29 (.090)
26	39.24 (1.545)	33.32 (1.312)	24.56 (.967)	2.29 (.090)
44	53.04 (2.088)	47.04 (1.852)	38.30 (1.508)	2.29 (.090)
62	69.34 (2.730)	63.50 (2.500)	54.76 (2.156)	2.41 (.095)

#### How to order



For special request, please consult factory

# Do not hesitate to contact us for further information

# **Amphenol**

#### **Amphenol IT & Communication Products**

Block A3/A4, The 4th Industrial District of Industrial Headquarters, Dong Keng Road Gong Ming Town, Shen Zhen China Fax:+86(0)755 2754 9955

Technical Support
Tel:+86(0)755 2717 7945
Info-dsub@amphenol.com.cn
http://www.dsubconnector.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

### Amphenol:

L77HDA26SD1CH4FC309MT L77HDB44SD1CH4RSAG L77HDA26SD1CH4F L77HDC62SD1CH3RC309
L77HDB44SD1CH4FC309 L77HDC62SD1CH3FC309 L77HDB44SD1CHC309 L77HDB44SD1CH3RC309
L77HDA26SD1CH3FC309 L77HDC62SD1CH4FC309 L77HDE15SD1CH3RC309 L77HDE15SD1CH4RC309
L77HDA26SD1CH3RC309 L77HDB44SD1CH4RC309 L77HDC62SD1CH4RC309 L77HDE15SD1CH4FC309
L77HDA26SD1CH4FC309 L77HDB44SD1CH3FC309 L77HDA26SD1CH4RC309 L77HDE15SD1CH3FC309
L77HDB44SD1CH4R L77HDA26SD1CH4R L777HDC62PD1CH3F L77HDE15SD1CH4F L77HDE15SD1C
L77HDA26SD1CH3F L777HDC62PD1CH4R L777HDA26PD1CH4R L77HDE15SD1CH3R L777HDC62PD1CH3R
L777HDA26PD1CH3F L777HDB44PD1CH3R L77HDB44SD1CH L77HDC62SD1CH3R L77THDE62SD1CH3F
L777HDE15PD1CH4F L777HDB44PD1CH3R L77HDB44SD1CH L77HDB44SD1CH4F L777HDE15PD1CH4R
L77HDC62SD1C L777HDB44PD1CH3F L77HDB44SD1CH3R L77THDE15PD1CH3R L77THDB44PD1CH4R
L77HDC62SD1CH4F L77HDA26SD1CH4FT L77HDB44SD1CH3R L77THDE15PD1CH3F L77THDB44PD1CH4R
L77HDC62SD1CH3F L77HDB45D1CH4R L77HDC62SD1CH3R L77THDB44PD1CH4R
L77HDC62SD1CH4F L77HDA26SD1CH4FT L77HDC62SD1CH4R L77THDB44PD1CH4F L77THDC62PD1CH4F
L77HDC62SD1CH4F L77HDA26SD1CH4R L77HDE15SD2CH4R L77THDB44PD1CH4F L77THDB44SD1CH3F
L77HDD78SD1CH4R L77THDA26PD1CH4F L77THDE15SD2CH4R L77THDB44PD1CH4F L77THDB44SD1CH3F
L77HDD78SD1CH4R L77THDA26PD1CH4F L77THDE15SD0CH4FNS L77THDE15SD0CH4FNSBL
L77HDE15SD1CH4FNNGA L77HDE15SD1CH4RNNGA L77HDE15SD0CH4RNSBL