

Specification Sheet

Part Number: 156-00592



Cable Tie & Edge Clip, 8.0" Long, EC23, 3-6 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg

| | |
|---------------------|--|
| Article Number | 156-00592 |
| Type | T50REC23 |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.• Edge Clip provides low insertion force and high extraction force ideal for assembly environments.• Two piece assembly allows the mount to slide along the strap ensuring proper orientation. |
| Quantity Per | bag |

Product Description

The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

Short Description

Cable Tie & Edge Clip, 8.0" Long, EC23, 3-6 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg

Global Part Name

T50REC23-PA66UV/PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

8.0

Length L (Metric)

202.0

Fixation Method

EdgeClip, sideways, assembled, 2 piece

Identification Plate Position

none

Variant

Inside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.20

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

2.0

Bundle Diameter Max (Metric)

50.0

Thickness T (Imperial)

0.05

| | |
|---------------------------------------|---|
| Thickness T (Metric) | 1.2 |
| Height H (Imperial) | 0.05 |
| Height H (Metric) | 1.2 |
| Panel Thickness Min(Imperial) | 0.12 |
| Panel Thickness Max(Imperial) | 0.24 |
| Panel Thickness Min (Metric) | 3.0 |
| Panel Thickness Max (Metric) | 6.0 |
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 UV-stabilized (PA66UV) |
| Material Shortcut | PA66HIRHS PA66UV |
| Material Cable Tie | Polyamide 6.6 UV-stabilized (PA66UV) |
| Flammability | UL 94 HB |
| Operating Temperature (Metric) | -40°F to +230°F (-40°C to +110°C) -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |

Customs Number

3926909987

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)