



Dimensions in Inches (mm)



Plugs

Watertight Safety-Shroud®

IP66 SUITABILITY UL Type 4x, 12

| Description | Cord Dia. | Catalog Number | | |
|--|-----------------------|------------------|------------------|---|
| Black Valox® housing, white Valox® clamps. | .325"-.930" (9-24) | HBL2611SW | HBL2621SW | - |

Safety-Shroud®

IP20 SUITABILITY

| Description | Cord Dia. | Catalog Number | | |
|---|-----------------------|-----------------|-----------------|---|
| Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies. | .360"-.930" (9-24) | HBL2611S | HBL2621S | - |

Note: See page B-40 for accessories.

Insulgrip®

IP20 SUITABILITY

| Description | Cord Dia. | Catalog Number | | | |
|---|-----------------------|------------------|------------------|----------------|---|
| Black and white nylon. | .360"-.930" (9-24) | HBL2611 | HBL2621 | HBL2631 | |
| Heat stabilized, gray nylon, 220° F (104° C). | .360"-.930" (9-24) | HBL2611F | HBL2621F | | - |
| Corrosion resistant, yellow nylon. | .360"-.930" (9-24) | HBL26CM11 | HBL26CM21 | | - |
| All black nylon. | .360"-.930" (9-24) | HBL2611BK | HBL2621BK | | - |

Note: See page B-51 for accessories.

Valise®

IP20 SUITABILITY

| Description | Cord Dia. | Catalog Number | | | |
|------------------------------------|----------------------------|-------------------|-------------------|--|---|
| Yellow nylon. | .590"-.930" (15.0-23.6) | HBL2611VY | HBL2621VY | | - |
| Corrosion resistant, yellow nylon. | .590"-.930" (15.0-23.6) | HBL26CM11V | | | - |
| Black nylon. | .590"-.930" (15.0-23.6) | HBL2611VBK | HBL2621VBK | | - |

Note: See page B-51 for accessories.

Flanged Inlets

Watertight Safety-Shroud®

IP66 SUITABILITY UL Type 4x, 12

| Description | Catalog Number | | |
|--|-------------------|------------------|---|
| Gray Valox® housing and flange. | HBL2615SW | HBL2625SW | - |
| Reverse service, gray Valox® housing and flange (use with HBL2613SR), (Not shown). | HBL2615SWR | | - |

Note: See page B-54 for accessories.

Insulgrip®

IP20 SUITABILITY

| Description | Catalog Number | | | |
|---|------------------|-----------------|----------------|---|
| Nylon casing, back wired. | HBL2615 | HBL2625 | HBL2635 | |
| Heat stabilized, gray nylon, 220° F (104° C). | HBL2615F | HBL2625F | | - |
| Nylon casing, weather protective, die cast aluminum, back wired, self closing lift cover. | HBL2615M3 | | | - |

Note: See page B-50 for accessories.

See pages B-69 and B-70 for technical information on Twist-Lock and Watertight Safety-Shroud devices.
 See page B-74 for technical information on Valise plugs and connectors.

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.